

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal T-Rex Power Extrémní Síla

Revision: 5/05/2015

Page 1 from 3

Reference nr DOP: 231112

Unique identification code of the product type:

Soudal T-Rex Power Extrémní Síla

Intended use or uses of the construction product:

Sealant for facade for interior application.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F -INT

System or systems of assesment and verification of consistency of performance of the construction product, as set out in Annex V:

System 4

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

WFR GENT, NB 1173 has carried out Determination of the Product Type under system 3 for reaction to fire.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal T-Rex Power Extrémní Síla

Revision: 5/05/2015

Page 2 from 3

Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 45%	
Elongation at break	≥ 25%	
Durability	Pass	

Conditioning:

Method B

Substrate:Aluminium
Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
BE-2300 Turnhout, 5/05/2015

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 5/05/2015

Page 3 from 3



NB 1173

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

15

Reference nr DOP: 231112

EN 15651-1: 2012

Sealant for facade for interior application.

Soudal T-Rex Power Extrémní Síla

EN 15651-1:2012: Type F -INT

Conditioning:

Method B

Substrate:

Aluminium

Mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 45%	
Elongation at break	≥ 25%	
Durability	Pass	